arXiv:math/0606723v1 [math.CA] 28 Jun 2006

Exact solution of a differential problem in analytical fluid dynamics: use of Airy's functions

Gianluca Argentini
gianluca.argentini@gmail.com
gianluca.argentini@riellogroup.com
Research & Development Department
Riello Burners, 37048 San Pietro di Legnago (Verona), Italy

June 2006

Abstract

Treating a boundary value problem in analytical fluid dynamics, translation of 2D steady Navier-Stokes equations to ordinary differential form leads to a second order equation of Riccati type. In the case of a compressible fluid with constant kinematic viscosity along streamlines, it is possible to find an exact solution of the differential problem by rational combination of Airy's functions and their derivatives.

1 Ordinary differential form of Navier-Stokes equations

Suppose to have a 2D steady flow of a fluid. Let

$$\Phi : s \longmapsto (\phi_1(s), \phi_2(s)) = (x, y) \tag{1}$$

an admissible parameterization ([5]) for each streamline, with $\Phi : [a, b] \rightarrow \mathbb{R}^2$ for some suitable values a and b such that $\Phi(a)$ is the initial point of the streamline, $\Phi(b)$ is the end point in the considered geometrical domain. Then, if $\mathbf{v} = (v_1, v_2)$ is the flow velocity field, by definition of streamline there is a scalar function $f = f(s)$ such that

$$(v_1, v_2) = f(s)(\dot{\phi}_1(s), \dot{\phi}_2(s)) \tag{2}$$

where $\dot{\phi}$ is the derivative of ϕ.

Remark. The author is developing a more general model of parameterization for Navier-Stokes equations, in the case 3D too, under less restrictive hypothesis than those formulated in this work.

Suppose that $f(s) \neq 0$, $\dot{\phi}_1(s) \neq 0$ for all s along the streamline, that is $v_1 \neq 0$, and let $\mathbf{u} = \mathbf{v} \circ \phi$. Then

Proposition 1 *Along a streamline* $s \longmapsto \phi(s)$ *the following relation holds:*

$$\mathbf{v} \cdot \nabla v_1 = \frac{1}{\dot{\phi}_1} u_1 \dot{u}_1 \tag{3}$$

Dim. Using chain rule we have

$$\dot{u}_1 = \frac{\partial v_1}{\partial x}\dot{\phi}_1 + \frac{\partial v_1}{\partial y}\dot{\phi}_2 \tag{4}$$

But from (2)

$$\dot{\phi}_2 = \frac{v_2}{v_1}\dot{\phi}_1 \tag{5}$$

therefore

$$\dot{u}_1 = \frac{\dot{\phi}_1}{v_1}\left[v_1\frac{\partial v_1}{\partial x} + v_2\frac{\partial v_1}{\partial y}\right] \tag{6}$$

Then (3) follows from the fact that along the streamline $u_1(s) = v_1(\phi(s))$. $\square$

Now let ϕ invertible, that is $\exists\ g : \phi([a,b]) \to [a,b]$ such that $s = g(\phi(x,y))$ when $(x,y) = \phi(s)$. Then

Proposition 2 *Along a streamline the following relation holds:*

$$\Delta v_1 = (\nabla g \cdot \nabla g)\ddot{u}_1 + (\Delta g)\dot{u}_1 \tag{7}$$

Dim. From definition, we have $\mathbf{v} = \mathbf{u} \circ g$, therefore $\nabla v_1 = \dot{u}_1 \nabla g$. Then

$$\frac{\partial^2 v_1}{\partial x^2} = \ddot{u}_1\left(\frac{\partial g}{\partial x}\right)^2 + \dot{u}_1\left(\frac{\partial^2 g}{\partial x^2}\right) \tag{8}$$

and

$$\frac{\partial^2 v_1}{\partial y^2} = \ddot{u}_1 \left(\frac{\partial g}{\partial y}\right)^2 + \dot{u}_1 \left(\frac{\partial^2 g}{\partial y^2}\right) \tag{9}$$

therefore the thesis follows by summing the two previous expressions. □

The following Proposition holds for a scalar function $p = p(x, y)$:

Proposition 3 *Let $q = p \circ \phi$. Along a streamline:*

$$\Delta p = \dot{q}(\Delta g) \tag{10}$$

Dim. From $q = p \circ \phi$ follows $p = q \circ g$. Then, using chain rule,

$$\frac{\partial p}{\partial x} = \frac{dq}{ds}\frac{\partial g}{\partial x} \tag{11}$$

and analogous equation for y-differentiation. □

Now let ρ the density, μ the dynamic viscosity and $\mathbf{f}$ the body force per unit volume of fluid. Then the Navier-Stokes equations for the steady flow are (see [1])

$$\rho(\mathbf{v} \cdot \nabla \mathbf{v}) = -\nabla p + \rho \mathbf{f} + \mu \Delta \mathbf{v} \tag{12}$$

Identifying not derived functions $h(x, y)$ with their composition $h \circ \phi$ and using simple substitutions, from previous Propositions and (2) we can state the *ordinary differential form* of Navier-Stokes equations:

$$\begin{aligned} \rho \frac{1}{\dot{\phi}_1} u_1 \dot{u}_1 &= \rho f_1 - \dot{q}\frac{\partial g}{\partial x} + \mu(\nabla g \cdot \nabla g)\ddot{u}_1 + \mu(\Delta g)\dot{u}_1 \\ u_2 &= \frac{\dot{\phi}_2}{\dot{\phi}_1} u_1 \end{aligned} \tag{13}$$

Note that, if the streamlines $\phi = (\phi_1, \phi_2)$ are known, from equation (13) it could be possible calculate u_1. But what about the physical meaning of this solution? We make now some considerations about conservation of mass.

2 About continuity equation

In the case of incompressible flow, the differential form of this equation is simply $\nabla \cdot \mathbf{v} = 0$ ([1] or [6]). In this case, from $\mathbf{v} = \mathbf{u} \circ g$, follows that $\partial_x v_1 = \dot{u}_1 \partial_x g$ and $\partial_y v_2 = \dot{u}_2 \partial_y g$, therefore along a streamline the continuity equation is

$$\dot{\mathbf{u}} \cdot \nabla g = 0 \tag{14}$$

But it is possible, in the hypothesis $\dot{\phi}_1 \neq 0$ along the streamline, to rewrite this equation using only u_1:

Proposition 4 *If $\dot{\phi}_1(s) \neq 0 \ \forall \ s$, the continuity equation for incompressible flow is*

$$\dot{u}_1 + \left[\ddot{\phi}_2 - \frac{\dot{\phi}_2}{\dot{\phi}_1} \ddot{\phi}_1 \right] \frac{\partial g}{\partial y} u_1 = 0 \tag{15}$$

Dim. Differentiating the identity $g(\phi(s)) = s$ respect to variable s, we have $\nabla g \cdot \dot{\phi} = 1$. Then

$$\partial_x g = \frac{1}{\dot{\phi}_1} - \frac{u_2}{u_1} \partial_y g \tag{16}$$

Substituting this formula in the continuity equation (14) and using $u_1 \dot{\phi}_2 = u_2 \dot{\phi}_1$, we obtain the new identity

$$\dot{u}_1 + [\dot{\phi}_1 \dot{u}_2 - \dot{\phi}_2 \dot{u}_1] \partial_y g = 0 \tag{17}$$

Differentiating the relation $u_2 = \frac{\dot{\phi}_2 u_1}{\dot{\phi}_1}$, follows that

$$\dot{u}_2 = \frac{\ddot{\phi}_2 u_1 + \dot{\phi}_2 \dot{u}_1}{\dot{\phi}_1} - \frac{\ddot{\phi}_1 \dot{\phi}_2 u_1}{\dot{\phi}_1^2} \tag{18}$$

from which the relation (15) is obtained eliminating $\dot{u}_2$ in (17). $\Box$

Remark. Suppose the streamlines are straight lines expressed by the parameterization $\phi_1(s) = s$, $\phi_2 = k$, with k real constants. Then $\dot{\phi}_1 = 1$ and $\dot{\phi}_2 = 0$, and from (15) the continuity equation is simply $\dot{u}_1 = 0$. Then the velocity field is constant along a streamline, as known for incompressible rectilinear flow (see e.g. [6]).

As we would investigate existence of non trivial solutions to Navier-Stokes equations (13) in the simple case $x = \phi_1(s) = s$, we have $g_x = 1$ and $g_y = 0$, therefore in the incompressible case from previous Proposition follows that u_1 is constant. For a more interesting and realistic solution we assume that flow is steady but with spatially variable density.

3 A steady compressible flow

Consider a 2D steady flow where streamlines are parameterizable by the following expressions

$$x = \phi_1(s) = s, \qquad y = \phi_2(s) = \phi_2(x) \tag{19}$$

where ϕ_2 is invertible on an interval $[0, L]$, that is for each streamline exists a function $g : \phi([0, L]) \to [a, L]$ such that $s = g(x, y) = x$. The function ϕ_2 and g can depend on the single streamline. Note that $\dot{\phi}_1 = 1$, $\nabla g = (1, 0)$ and $\Delta g = 0$, therefore from (13) the Navier-Stokes equations along a streamline become

$$\rho u_1 \dot{u}_1 = \rho f_1 - \dot{q} + \mu \ddot{u}_1, \qquad u_2 = \dot{\phi}_2 u_1 \tag{20}$$

Suppose that x-component f_1 of body force $\mathbf{f}$ is constant. Along a streamline we can made the realistic hypothesis that $\rho(s) \neq 0 \ \forall s$; dividing the two members by ρ we obtain

$$u_1 \dot{u}_1 = f_1 - \frac{\dot{q}}{\rho} + \nu \ddot{u}_1 \tag{21}$$

where $\nu = \frac{\mu}{\rho}$ is the kinematic viscosity (see [1]). At this point we suppose that, along a single streamline, ν and the quantity $\frac{\dot{q}}{\rho}$ are constant, with values depending on streamline. The latter, equivalent to $p = k_1 \int \rho + k_2$, can be view as a constitutive equation about the fluid.

4 An analytical resolution

In this section we try to find a general exact solution of the non linear differential equation $(21)_1$. Integrating on the independent variable s and then dividing by ν, we have

$$\dot{u}_1 = \frac{1}{2\nu} u_1^2 + \frac{1}{\nu} \left(\frac{\dot{q}}{\rho} - f_1 \right) s + \frac{c}{\nu} \tag{22}$$

where c is an arbitrary constant. This is a first order differential equation of *Riccati* type (see [2] or [3]). Applying the transformation

$$u_1 = -2\nu \frac{\dot{z}}{z} \tag{23}$$

we translate previous equation into (see [2])

$$\ddot{z} + \frac{1}{2\nu^2}\left[\left(\frac{\dot{q}}{\rho} - f_1\right)s + c\right]z = 0 \tag{24}$$

This is a form of *Airy*'s type equation (see [3] and [4]) and its general solution is (see [4])

$$z(s) = c_1 Ai(t) + c_2 Bi(t) \tag{25}$$

where

$$\begin{aligned} t &= -\frac{as+b}{(-a)^{\frac{2}{3}}} && (26)\\ a &= \frac{1}{2\nu^2}\left(\frac{\dot{q}}{\rho} - f_1\right) && (27)\\ b &= \frac{c}{2\nu^2} && (28) \end{aligned}$$

while $Ai(t)$ and $Bi(t)$ are *Airy's functions* (see e.g. [7]), linearly independent solutions of *Airy's equation* $\ddot{y} - ty = 0$ which appears in optics and quantum mechanics phenomena.

Using transformation (23), the exact solution of Navier-Stokes equation (22) along a streamline is

$$u_1 = 2\nu(-a)^{\frac{1}{3}} \frac{c_1 Ai'(t) + c_2 Bi'(t)}{c_1 Ai(t) + c_2 Bi(t)} \tag{29}$$

where $Ai'(t)$ and $Bi'(t)$ are the derivative of Ai and Bi.

Note that this solution has physical meaning only if $a < 0$. Assuming that inflow zone is at $s = 0$, usually pressure drops down towards outflow, so that we can assume $\dot{q} < 0$. Also, we assume $f_1 > 0$, hence the condition $a < 0$ is satisfied.

Also, note that with our assumptions u_1 doesn't depend on the streamline parametric representation $(x, y) = \phi(s)$; the flow velocity field depends on ϕ through u_2 component by relation $u_2 = \dot{\phi}_2 u_1$.

5 A boundary value problem

The general solution (29) depends on three constants of integration: c_1, c_2 and, from (22), c. Suppose we want to resolve a boundary value problem for equation (21) with $u_1(0) = u_{10}, \dot{u}_1(0) = \dot{u}_{10}$ and $u_1(L) = u_{1L}$. The first two conditions, using (22) at $s = 0$, give the value of c. Then, noting that for $t \in \mathbb{R}$ Airy's functions $Ai(t)$ and $Bi(t)$ have real values (see [7]), the other two constants c_1 and c_2 can be found solving the algebraic system $u_1(0) = u_{10}$, $u_1(L) = u_{1L}$.

References

[1] Batchelor, G.K. *An introduction to fluid dynamics*, Cambridge Mathematical Library, Cambridge University Press (2000)

[2] Boyce, W.E. and DiPrima, R.C. *Elementary Differential Equations*, 6th edition, Wiley, (1996)

[3] Braun, W.H. and Goldstein, M.E. *Advanced Methods for the solution of Differential Equations*, NASA SP-316, Washington (1973)

[4] Coombes, K.; Hunt, B.; Lipsman, R.; Osborn, J. and Stuck, G. *Differential Equations with Mathematica*, 2nd edition, John Wiley & Sons, Inc. (1998)

[5] Lipschutz, M. *Differential Geometry*, MacGraw-Hill, New York (1969)

[6] Malek-Madani, R. *Advanced Engineering Mathematics*, Addison-Wesley, (1998)

[7] Temme, N.M. *Special functions: an introduction to the classical functions of mathematical physics*, J.Wiley, New York (1996)